

Forklift Seat Belts

Seat Belts for Forklift - This guideline reason is to describe the Regulation necessities for the application of driver restraints or seatbelts on lift trucks. It is the employers' accountability to be able to make sure that each and every machinery, piece of equipment and device inside the workplace is selected and utilized correctly and worked in accordance with the manufacturer's directions.

Rough Terrain lift trucks need to meet the guidelines of ANSI Standard ASME B56.6-1992 in regards to their inspection, fabrication, use, design and maintenance.

Mobile machines such as side boom tractors with a Rollover Protective Structure (ROPS), should contain seat belts which meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If any mobile machine includes seat belts required by law, the driver and subsequent passengers need to make sure they make use of the belts whenever the motor vehicle is in motion or engaged in operation because this could cause the machinery to become unstable and thus, not safe.

When a seat belt or different driver restraint is required on a forklift.

While operating a lift truck, the seat belt requirements will depend on several factors. Contributing factors to this determination may include whether the the forklift is equipped along with a Rollover Protective Structure, the kind of lift truck itself and the year the forklift was manufactured. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

In the case of powered industrial trucks, ANSI Standard ASME B56.1-1993 refers to an operator restraint device, enclosure or system. An operator restraint device, enclosure or system is designed to be able to aid the operator in lowering the risk of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The restraint device or system could comprise a seat belt, while a seat belt is not necessarily a part of such device or system.